



NOTE:

1. Electrical test:

- (1). 100% open short & miss wire test;
- (2). Insulation resistance: DC 300V 10MΩ;
- (3). Conductor resistance: 3Ω Max;
- (4). Transfer speed: 5Gbps, Current: 3A Max;

2. RoHS 2.0 AND REACH COMPLIANT

MATERIAL LIST:

④	OUTER MOLD	PVC 88A COLOR White	2	
③	USB C TYPE	USB C/M Solder Type, Black PBT Insulation, The Pin Gold Plating, the shell for Nickel Plating	1	
②	USB A TYPE	USB A/M, BLUE INSULATION, THE PIN GOLD PLATING, THE SHELL FOR NICKEL PLATING	1	
①	CABLE	(30AWG TC*1P+D+NYLON)*2C+30AWG TC*1P+23AWG TC+NYLON)*2C+ NYLON+AL+B JACKET: 70P PVC White OD: 4.5±0.2mm	1	

ITEM NO	LENGTH
11.99.9035	2000±40mm
11.99.9036	3000±50mm

DESC. VALUE USB 3.2 AM-Type C Male Cable

NO.	PARTS NAME	SPECIFICATION DESCRIPTION	QT' Y	REMARK
			2021-11-03	A
BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.

SECOMP