



Datenblatt - Fiche technique - Data sheet


21.15.2944



ROLINE Patchkabel Kat.6 UTP, Component Level, LSOH, blau, 0,3 m

Cordon ROLINE UTP Cat.6, LSOH, Component Level, bleu, 0,3 m

ROLINE UTP Cable Cat.6 Component Level, LSOH, blue, 0.3 m



1. ELECTRICAL TEST:

- (1). 100% OPEN SHORT & MISS WIRE TEST;
- (2). INSULATION RESISTANCE:DC 250V 20M OHM MIN;
- (3). CONTACTOR RESISTANCE:30 OHM MAX

2. PRINTING:GHMT® roline CAT.6 U/UTP COMPONENT PATCH CORD LSZH 250MHz ISO/IEC 11801 & EN 50173-1 & ANSI/TIA-568-C.2

- 3. 100% Component Patch cord Test PASS
- 4. Minimum bending radius:50mm

MATERIAL LIST

⑥	LABEL	NO DRY GLUE LABEL	1PCS	
⑤	MINI TIE	PE MINI TIE (POSSESS METAL)	2PCS	
④	POLYETHYLENE BAG	POLYETHYLENE BAG	1PCS	
③	OVER MOLD	88A PVC blue	2PCS	
②	CONNECTOR	RJ45 8P8C' S UNSHIELDED PIN GOLD PLATED 3u", Transparent RED	2PCS	
①	CABLE	U/UTP CAT.6 24AWG (BC*1P)*4+CROSS + JACKET LSOH OD=6.0±0.2MM	1PCS	
NO.	PARTS NAME	SPECIFICATION STANDARD	QT' Y	REMARK

COLOUR:blue (PANTONE:647C)		
ITEM NO.	LENGTH (L)	TOLERANCE (T)
21. 15. 2944	300mm	±10mm
21. 15. 2540	500mm	±15mm
21. 15. 2541	1000mm	±30mm
21. 15. 2544	1500mm	±45mm
21. 15. 2542	2000mm	±60mm
21. 15. 2543	3000mm	±90mm
21. 15. 2545	5000mm	±150mm
21. 15. 2546	7500mm	±210mm
21. 15. 2547	10000mm	±300mm
21. 15. 2548	15000mm	±450mm
21. 15. 2549	20000mm	±600mm

ITEM NO.	21. 15. 2944	21. 15. 2540	21. 15. 2541	21. 15. 2542	21. 15. 2543
21. 15. 2544	21. 15. 2545	21. 15. 2546	21. 15. 2547	21. 15. 2548	21. 15. 2549
DESC.	ROLINE UTP PatchCord CAT. 6, LSOH, Comp. Level, blue				

BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.

2016-10-20 A

