



**Note:**

**RoHS 2.0 and REACH Compliant**

Test Grade Designation:Each to Reference		
Grade IL/RL	MULTI-MODE	
Insertion Loss (IL)	≤0.3dB	IEC 61300-3-4
Return Loss (RL)	UPC≥30dB	IEC 61300-3-6
Test Wavelength	850nm	
End face inspection	×400	

**MATERIAL LIST:**

⑧	Ring 1 2	4	
⑦	Black Heat Shrink Tube	2	
⑥	LC Duplex Clip Erika violet	2	
⑤	LC Transparent Dust cap	4	
④	LC Erika violet Connector	4	
③	LC White 3.0mm Boot	4	
②	LC/UPC SM Ceramic Ferrule	4	
①	Fiber Optical Cable Simplex Ø3.0 OM4 50/125um Erika violet LSZH ,Armored (only Stainless steel spiral pipe, no Stainless Steel braiding)	Xm	

ITEM NO.	LENGTH
21.15.8610	1m
21.15.8611	2m
21.15.8612	3m
21.15.8613	5m
21.15.8614	7m
21.15.8615	10m
21.15.8616	15m
21.15.8617	20m

DESC. Roline FO Jumper Armoured Cable, OM4 Duplex, LSOH, LC-LC

NO	SPECIFICATION STANDARD	QT'Y	REMARK
BY	CHK	REVISION RECORD MODIFICATIONS	DATE REV.



NEW 2022-01-20 A