



Product Specification

SuperPod WiFi 6E

Product code: 945-1107







WiFi-Interfaces

Tri-band, tri-concurrent radio operation



4x4 MIMO 802.11ax, 20/40/80/160 MHz • 6 GHz : ■ 5 GHz : 4x4 MIMO 802.11ax. 20/40/80 MHz • 2.4 GHz : 2x2 MIMO 802.11ax, 20/40 MHz



Ethernet Interfaces

- 1 port 100/1000 Base-T
- 1 port 2.5G Base-T Ethernet (WAN or LAN config)



IoT-Radio

Bluetooth Low Energy



Power

Power Supply 100 to 240VAC, 50/60Hz

Plug Type Swiss Plug

Power Consumption : 11W Standby, 16W Average, 26W Maximum



Environment



Operating Temperature 0°C to 40°C Operating Relative Humidity : 10% to 90%

Storage Conditions -20°C to 70° C 10% to 90% (Relative Humidity)



Networking and Connectivity

Networking Modes: Auto-sensing Router or Bridge mode

Firewall and Networking: NAT, DHCP server, UPnP, client IP reservation, port

forwarding

Home SSIDs: Managed with HomePass® or WorkPass® Guest Access: Managed with HomePass® or WorkPass® Authentication/Encryption: WPA2-PSK (KRACK Patched) / WPA3





Packaging Content

- High-end single package with 1 SuperPod WiFi 6E
- Ethernet cable




Size and Weight

Size:


Weight:

106mm W x 97mm H x 40mm D (not including plug)

290g



106mm



97 mm

87mm



Interface



