



PIN OUT

CN1 (568B) CN2 (568B)



NOTE:

- ELECTRICAL TEST:100% OPEN SHORT, MISS WIRE TEST
- FLUKE Channel TEST:
TEST LIMIT:ISO11801 Channel Class Ea
- Working temperature:-20°C~+75°C
Storage temperature:-20°C~+80°C
- RoHS AND REACH compliant
- PRINT WORD:CAT6A U/UTP 4x2x32AWG/7 RECYCLED PVC ISO11801 & EN50173 & ANSI/TIA568. 2-D
- Minimum of the bending radius is 4*OD (Suitable for all meters)

MATERIAL LIST:

③	OVER MOLD	RECYCLED PVC BLUE PANTONE 647C	2	
②	PLUG	RJ45 8P8C UNSHIELDED PLUG, PIN GOLD PLATED 3U", COLOUR:TRANSPARENT GREEN	2	
①	CABLE	CAT. 6A U/UTP CABLE (32AWG BC*1P)*4P JACKET:RECYCLED PVC BLUE PANTONE 647C OD:3.4±0.2MM	1	
NO.	PARTS NAME	SPECIFICATION DESCRIPTION	QT'Y	REMARK
		NEW	2023-11-30	A
BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.

21.45.3447	ROLINE RECYCLED UTP PatchCord, Cat6A/Cl.EA, SLIM, blue, 5m	5000±100	57.3%
21.45.3446	ROLINE RECYCLED UTP PatchCord, Cat6A/Cl.EA, SLIM, blue, 3m	3000±50	57.2%
21.45.3445	ROLINE RECYCLED UTP PatchCord, Cat6A/Cl.EA, SLIM, blue, 2m	2000±30	57.1%
21.45.3444	ROLINE RECYCLED UTP PatchCord, Cat6A/Cl.EA, SLIM, blue, 1.5m	1500±30	57.0%
21.45.3443	ROLINE RECYCLED UTP PatchCord, Cat6A/Cl.EA, SLIM, blue, 1m	1000±20	56.0%
21.45.3442	ROLINE RECYCLED UTP PatchCord, Cat6A/Cl.EA, SLIM, blue, 0.5m	500±20	55.5%
21.45.3441	ROLINE RECYCLED UTP PatchCord, Cat6A/Cl.EA, SLIM, blue, 0.3m	300±10	54.0%
21.45.3440	ROLINE RECYCLED UTP PatchCord, Cat6A/Cl.EA, SLIM, blue, 0.15m	150±10	53.0%
ITEM NO.	DESC.	LENGTH (mm)	The proportion of RECYCLED certification materials

SECOMP