



TP-Link ER7406 Kabelrouter Gigabit Ethernet Schwarz

Marke : TP-Link

Artikel-Code: ER7406

Produktname : ER7406

TP-Link ER7406. Netzstandard: IEEE 802.1D, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z, Ethernet Schnittstellen Typ: Gigabit Ethernet, Ethernet LAN Datentransferraten: 10,100,1000 Mbit/s. Unterstützte Sicherheitsalgorithmen: 128-bit AES, 192-bit AES, 256-bit AES, DES, MD5, SHA-1, SHA-2, SHA-384, SHA-512. Flash-Speicher: 128 MB, Speicherkapazität: 512 MB, Interner Speichertyp: DDR4. Produktfarbe: Schwarz. Stromverbrauch (max.): 7,5 W, AC Eingangsspannung: 100 - 240 V, AC Eingangsfrequenz: 50/60 Hz



WAN-Verbindung		Technische Details	
Ethernet-WAN *	✓	Konformitätsbescheinigungen	CE, Eidgenössische Kommunikationskommission (FCC), RoHS
DSL-WAN *	✗		
SIM-Karten-Slot *	✗		
3G/4G USB Modem-Kompatibilität *	✓		
SFP-WAN *	✓		
Netzwerk		Merkmale	
Netzstandard *	IEEE 802.1D, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Flash-Speicher	128 MB
Ethernet Schnittstellen Typ *	Gigabit Ethernet	Speicherkapazität	512 MB
Ethernet LAN Datentransferraten	10,100,1000 Mbit/s	Interner Speichertyp	DDR4
Statische Route	✓	Unterstützt Windows-Betriebssysteme	Windows 10, Windows 2000, Windows 7, Windows 8, Windows 8.1, Windows 98SE, Windows NT, Windows Vista, Windows XP
VLAN-Unterstützung	✓	Unterstützt Mac-Betriebssysteme	✓
Management-Funktionen		Unterstützte Linux-Betriebssysteme	✓
Web-basiertes Management *	✓	Design	
Reset-Knopf	✓	Produktfarbe *	Schwarz
Anschlüsse und Schnittstellen		Rack-Einbau	✓
Anzahl Ethernet-LAN-Anschlüsse (RJ-45) *	5	Energie	
Anzahl installierten SFP Module	1	Stromverbrauch (max.)	7,5 W
Anzahl der USB-Anschlüsse	1	AC Eingangsspannung	100 - 240 V
Protokolle		AC Eingangsfrequenz	50/60 Hz
DMZ-Unterstützung	✓	Betriebsbedingungen	
DHCP-Server *	✓	Betriebstemperatur	0 - 50 °C
Sicherheit		Temperaturbereich bei Lagerung	-40 - 70 °C
Unterstützte Sicherheitsalgorithmen *	128-bit AES, 192-bit AES, 256-bit AES, DES, MD5, SHA-1, SHA-2, SHA-384, SHA-512	Relative Luftfeuchtigkeit in Betrieb	10 - 90%
URL-Filterung	✓	Luftfeuchtigkeit bei Lagerung	5 - 90%
DoS Attacken Prävention	✓	Gewicht und Abmessungen	
ARP-Angriffsverhütung	✓	Breite	294 mm
ICMP-Angriffsverhütung	✓	Tiefe	140 mm
		Höhe	44 mm
		Verpackungsdaten	
		Mitgelieferte Kabel	AC

Sicherheit

Anzahl VPN-Tunnels 50

Verpackungsdaten

Schnellinstallationsanleitung ✓



8885020622300

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 23-AUG-2024. Prints or copies of Information are only valid on the printed Publication date