



## TP-Link Omada EAP673 WLAN Access Point 5400 Mbit/s Weiß Power over Ethernet (PoE)

Marke : TP-Link

Produktfamilie: Omada

Artikel-Code: EAP673

Produktname : EAP673

TP-Link Omada EAP673. 2,4 GHz, 5 GHz, Maximale Datenübertragungsrate: 5400 Mbit/s. Unterstützte Sicherheitsalgorithmen: SNMP, SNMPv2, SNMPv3, WPA-Enterprise, WPA-Personal, WPA2-Enterprise, WPA2-Personal, WPA3-Enterprise. Ethernet LAN Datentransferraten: 10,100,1000,2500 Mbit/s. Power over Ethernet (PoE). Produktfarbe: Weiß



Merkmale		Management-Funktionen	
2,4 GHz *	✓	Web-basiertes Management	✓
5 GHz *	✓	Syslog	✓
6 GHz *	✗	Upgradefähige Firmware	✓
Maximale Datenübertragungsrate *	5400 Mbit/s	<b>Anschlüsse und Schnittstellen</b>	
Maximale Datenübertragungsrate (2,4 GHz)	574 Mbit/s	Anzahl Ethernet-LAN-Anschlüsse (RJ-45) *	1
Maximale Datenübertragungsrate (5 GHz)	4804 Mbit/s	Gleichstrom-Anschluss (DC)	✓
Ethernet LAN Datentransferraten	10,100,1000,2500 Mbit/s	<b>Energie</b>	
Frequenzband	2.4 - 5 GHz	Power over Ethernet (PoE) *	✓
Netzstandard	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	DC Spannungsrange	12 V
Zahl der Benutzer	250 Benutzer	<b>Design</b>	
Automatische Kanalwahl	✓	Platzierung *	Zimmerdecke, Wand
Automatischer Kanalscan	✓	Produktfarbe *	Weiß
MIMO	✓	Reset-Knopf	✓
MIMO-Typ	Multi User MIMO	LED-Anzeigen	✓
VLAN-Unterstützung	✓	<b>Antenne</b>	
Virtuelle LAN-Funktionen	VLAN mapping	Antennentyp *	Intern
Ratenbeschränkung	✓	<b>Gewicht und Abmessungen</b>	
Unterstützung Datenflusssteuerung	✓	Breite	220 mm
Bandsteuerung	✓	Tiefe	220 mm
Airtime Fairness (ATF)	✓	Höhe	32,5 mm
Quality of Service (QoS) Support	✓	<b>Lieferumfang</b>	
BeamForming	✓	Menge pro Packung	1 Stück(e)
<b>Sicherheit</b>		Montageset	✓
Unterstützte Sicherheitsalgorithmen *	SNMP, SNMPv2, SNMPv3, WPA-Enterprise, WPA-Personal, WPA2-Enterprise, WPA2-Personal, WPA3-Enterprise	Schnellstartübersicht	✓
		<b>Betriebsbedingungen</b>	
		Relative Luftfeuchtigkeit in Betrieb	10 - 90%
		Betriebstemperatur	0 - 40 °C
		Temperaturbereich bei Lagerung	-40 - 70 °C
		Luftfeuchtigkeit bei Lagerung	5 - 90%



4895252506488



4895252506495



0840030711909



840030711909

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.